


## M6VLQ Pro Motherboard



- Socket 370
- Supports Intel Pentium III/Celeron Processor
- Supports FSB 66/100/133MHz

• Supports BIO-Remote 2 Technology

• Supports Charger Booster Technology

## M6VLQ Pro Specifcation

MEMORY	Support DDR 266 MHz 2 x DDR DIMM Memory Slot Max. Supports up to 2GB Memory
INTEGRATED VIDEO	VIA S3 UniChrome, On Board Graphic Max. Memory Share Up to 64MB
LAN	VIA VT6103 - 10/100 PHY
AUDIO CODEC	VIA VT1612A 6-Channel AC97 Audio
EXPANSION SLOT	3 x PCI Slot 1 x CNR Slots
REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 2 x USB Port 1 x COM Port 1 x Printer Port 1 x VGA Port 1 x LAN Port 3 x Audio Jacks

INTERNAL I/O

- 2 x USB Header
- 4 x IDE Connector
- 1 x Floppy Connector
- 1 x Front Panel Header
- 2 x CD-IN Header
- 1 x S/PDIF-Out Header
- 1 x Chassis Instruction Header

DIMENSION

Micro ATX Form Factor Dimension: 24.4cm X 19.2cm ( W x L )

## M6VLQ Pro OVERVIEW

\*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!