

U8668 Grand Motherboard



-
- Supports BIO-Remote 2 Technology
- Supports Charger Booster Technology

U8668 Grand Specification

FSB	Support FSB 533MHz
MEMORY	2 x SDRAM DIMM 133 Support DDR 266 MHz 2 x DDR DIMM Memory Slot Max. Supports up to 2GB Memory
INTEGRATED VIDEO	VIA S3 ProSavage, On Board Graphic Max. Memory Share Up to 32MB
STORAGE	4 x IDE Connector
LAN	VIA VT6103 - 10/100 PHY
USB	2 x USB 2.0 Port 2 x USB 2.0 Header
EXPANSION SLOT	3 x PCI Slot 1 x CNR Slots 1 x AGP X Slot

REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 2 x USB 2.0 Port 1 x COM Port 1 x Printer Port 1 x VGA Port 1 x LAN Port 3 x Audio Jacks
INTERNAL I/O	2 x USB 2.0 Header 4 x IDE Connector 1 x Floppy Connector 1 x IrDA Header 1 x Front Audio Header
DIMENSION	Micro ATX Form Factor Dimension: 24.4cm X 24.4cm (W x L)
U8668 Grand OVERVIEW	
*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!	