


P4M900-M7 FE Motherboard



- Socket LGA 775
- Supports Intel Core 2 Duo/Pentium D/Pentium 4/Celeron D/Celeron 400 Series Processor
- Supports FSB 533/800/1066MHz
- Support Intel Hyper-Threading Technology
- Due to the chipset limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® XP, Windows® XP 64-bit, Windows® Vista™ and Windows® Vista™ 64-bit.

P4M900-M7 FE Specification

CPU SUPPORT	Intel® Core™ 2 Duo Processor Intel® Pentium® Dual-Core Processor Intel® Pentium® D Processor Intel® Pentium® 4 Processor Intel® Celeron® D Processor Intel® Celeron® Processor 400 Sequence Maximum CPU TDP (Thermal Design Power) : 95Watt
FSB	Support FSB 533/800/1066MHz
MEMORY	Support DDR2 533/667 MHz 2 x DDR2 DIMM Memory Slot Max. Supports up to 4GB Memory
INTEGRATED VIDEO	VIA Chrome9 HC IGP, On Board Graphic Max. Memory Share Up to 256MB
STORAGE	2 x SATA Connectors 2 x IDE Connector Support SATA RAID: 0,1
LAN	Realtek RTL8201CL - 10/100 PHY
AUDIO CODEC	VIA VT1708B 6-Channel HD Audio

USB	4 x USB 2.0 Port 2 x USB 2.0 Header
EXPANSION SLOT	1 x PCI-E x16 Slot 1 x PCI-E x1 Slot 2 x PCI Slot
REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 4 x USB 2.0 Port 1 x COM Port 1 x VGA Port 1 x LAN Port 3 x Audio Jacks
INTERNAL I/O	2 x USB 2.0 Header 2 x SATA Connector 2 x IDE Connector 1 x Floppy Connector 1 x Front Audio Header 1 x Front Panel Header 1 x CD-IN Header 1 x CPU Fan Connector 1 x System Fan Connector 1 x Printer Port Header
DIMENSION	Micro ATX Form Factor Dimension: 19 cm X 24.4 cm (W x L)
OS SUPPORT	Supports Windows 2000 / XP / Vista
ACCESSORIES	1 x IDE Cable 1 x FDD Cable (Optional) 1 x SATA Cable (Optional) 1 x I/O Shield 1 x Fully Setup Driver CD 1 x Quick Guide

P4M900-M7 FE OVERVIEW

***The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!**