

TP75 Motherboard



- Support the Intel 3rd and 2nd generation Core i7 and Core i5 processors in the 1155 package
- Intel B75 single chip architecture
- Support 2-DIMM DDR3-1600/1333/1066 up to 16G maximum capacity
- 100% X.D.C solid capacitor

TP75 Specifcation

CPU SUPPORT	Intel® Core™ i7 LGA 1155 Processor Intel® Core™ i5 LGA 1155 Processor Intel® Core™ i3 LGA 1155 Processor Intel® Pentium® LGA 1155 Processor Intel® Celeron® LGA 1155 Processor Maximum CPU TDP (Thermal Design Power) : 95Watt
MEMORY	Support Dual Channel DDR3 1600/1333/1066 MHz 2 x DDR3 DIMM Memory Slot Max. Supports up to 16GB Memory
STORAGE	1 x SATA III Connector 5 x SATA II Connector
LAN	Realtek RTL8111F - 10/100/1000 Controller
AUDIO CODEC	Realtek ALC662 6-Channel HD Audio
USB	2 x USB 3.0 Port 1 x USB 3.0 Header 4 x USB 2.0 Port 2 x USB 2.0 Header Intel USB3.0 only support Win7 or later version

EXPANSION SLOT	1 x PCI-E 3.0 x16 Slot(supported by Core i5 -3xxx / Core i7 3xxx CPU) 1 x PCI-E 2.0 x16 Slot(x4) 2 x PCI-E 2.0 x1 Slot 2 x PCI Slot
REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 2 x USB 3.0 Port 4 x USB 2.0 Port 1 x COM Port 1 x LAN Port 3 x Audio Jacks
INTERNAL I/O	1 x USB 3.0 Header 2 x USB 2.0 Header 1 x SATA III Connector (6Gb/s) 5 x SATA II Connector (3Gb/s) 1 x Front Audio Header 1 x Front Panel Header 1 x S/PDIF-Out Header 1 x CPU Fan Connector 1 x System Fan Connector 1 x Printer Port Header
DIMENSION	ATX Form Factor Dimension: 30.5 cm x 21 cm (W x L)
OS SUPPORT	Supports Windows XP / Vista / 7 / 8
BUNDLE SOFTWARE	BIO-Remote2
ACCESSORIES	2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x User Manual
FEATURES	Windows 8 Ready Supports 100% Solid capacitor Supports Charger Booster Supports BIOS Online Update

TP75 OVERVIEW

***The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!**