

TB360-BTC PRO 2.0 Motherboard





- Supports 9^{th} & 8^{th} Generation Intel Core $^{\text{TM}}$ Processor
- Intel B360 single chip architecture
- Support 2-DIMM DDR4-1866/2133/2400/2666 up to 32G maximum capacity
- Support 12 x PCle 3.0 slots
- Support M.2 (6Gb/s) Connector
- Support HDMI Connector

Specifcation	
CPU SUPPORT	9 th Gen Intel Core i9 LGA 1151 Processor Socket 1151 for 9 th & 8 th Intel Core i7 / i5 / i3 / Pentium / Celeron processor * 8 th Generation Intel Core™ Processor Family only support 300-Series. * Please refer to www.biostar.com.tw for CPU support list.
MEMORY	Supports Dual Channel DDR4 1866/ 2133/ 2400/ 2666 2 x DDR4 DIMM Memory Slot, Max. Supports up to 32 GB Memory Each DIMM supports non-ECC 4/8/16GB DDR4 module * Please refer to www.biostar.com.tw for Memory support list.
INTEGRATED VIDEO	By CPU model Supports DX12 Supports HDCP
STORAGE	4 x SATA III Connectors (6Gb/s) 1 x M.2 (M Key) Socket: Supports M.2 Type 2242/ 2260/ 2280 SSD module Supports SATA III (6Gb/s) SSD
LAN	Realtek LAN Chip 10/ 100/ 1000 Mb/s auto negotiation, Half / Full duplex capability
AUDIO CODEC	ALC887 7.1 Channels, High Definition Audio
USB	6 x USB 3.1(Gen1) ports (4 on rear I/Os and 2 via internal header) 6 x USB 2.0 ports (2 on rear I/Os and 4 via internal header)
EXPANSION SLOT	11 x PCle 3.0 x1 Slot 1 x PCle 3.0 x16 Slot * Maximum VGA cards mining support are depending on VGA Driver or mining software.

1 x PS/2 Mouse 1 x PS/2 Keyboard 1 x VGA Port 1 x HDMI Port 1 x HDMI Port 1 x LAN port 2 x USB 2.0 Ports 4 x USB 3.1 (Gen1) Ports 3 x Audio Jack 4 x SATA III Connectors (6Gb/s) 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.1 (Gen1) Header (each header supports 2 USB 3.1 (Gen1) ports) 1 x 8-Pin Power Connector 2 x 24-Pin Power Connectors 2 x 6-Pin PCle Power Connectors 2 x 6-Pin PCle Power Connectors 1 x Front Panel Header 1 x Front Panel Header 1 x Front Panel Header 1 x Clear CMOS Header 2 x Stata Control 2 x Stata Control 2 x Stata Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA Cable 1 x // 0 Shield 1 x DVD Driver 1 x User Manual 2 x SATA		
2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.1(Gen1) Header (each header supports 2 USB 3.1(Gen1) ports) 1 x 8-Pin Power Connector 2 x 24-Pin Power Connectors 2 x 6-Pin PCle Power Connectors 1 x CPU Fan Connectors 1 x Front Panel Header 1 x Front Audio Header 1 x COM Serial Header 1 x Clear CMOS Header 1 x Clear CMOS Header CPU / System Fan Monitoring CPU / System Fan Monitoring System Fan Monitoring System Fan Monitoring DIMENSION ATX Form Factor Dimension: 29.5cm x 21.0cm (W x L) Supports Windows 10(64bit) / 11(64bit) *Biostar reserves the right to add or remove support for any OS with or without notice. BUNDLE SOFTWARE BUIlGuard 2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x User Manual	REAR I/O	1 x PS/2 Keyboard 1 x VGA Port 1 x HDMI Port 1 x LAN port 2 x USB 2.0 Ports 4 x USB 3.1(Gen1) Ports
CPU / System Fan Monitoring System Fan Monitoring Smart / Manual CPU Fan Control System Voltage Monitoring DIMENSION ATX Form Factor Dimension: 29.5cm x 21.0cm (W x L) Supports Windows 10(64bit) / 11(64bit) *Biostar reserves the right to add or remove support for any OS with or without notice. BUNDLE SOFTWARE BUILGUARD 2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x User Manual	INTERNAL I/O	2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.1(Gen1) Header (each header supports 2 USB 3.1(Gen1) ports) 1 x 8-Pin Power Connector 2 x 24-Pin Power Connectors 2 x 6-Pin PCle Power Connectors 1 x CPU Fan Connector 2 x System Fan Connectors 1 x Front Panel Header 1 x Front Audio Header 1 x COM Serial Header 1 x Clear CMOS Header
OS SUPPORT Supports Windows 10(64bit) / 11(64bit) *Biostar reserves the right to add or remove support for any OS with or without notice. BUNDLE SOFTWARE BullGuard 2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x User Manual	H/W MONITORING	CPU / System Fan Monitoring System Fan Monitoring Smart / Manual CPU Fan Control
SSUPPORT *Biostar reserves the right to add or remove support for any OS with or without notice. BUNDLE SOFTWARE BullGuard 2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x User Manual	DIMENSION	ATX Form Factor Dimension: 29.5cm x 21.0cm (W x L)
ACCESSORIES 2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x User Manual	OS SUPPORT	*Biostar reserves the right to add or remove support for any OS with or without
ACCESSORIES 1 x I/O Shield 1 x DVD Driver 1 x User Manual	BUNDLE SOFTWARE	BullGuard
FEATURES PCI-E Slot Detection BIOS Boot Screen	ACCESSORIES	1 x I/O Shield 1 x DVD Driver
	FEATURES	PCI-E Slot Detection BIOS Boot Screen

OVERVIEW



Intel B360 chipset

Give your small business a boost with the Intel® B360 Chipset and the 8th Generation Intel® Core™ processor. The Intel B360 chipset provides you with the power and performance you need for your small business, entertainment and digital life.



HD Audio

Provides high quality sound with minimal loss of audio fidelity.



HDMI 4K2K

The new 4K2K resolution enables high-definition image display with four times the resolution of full HD, 4K2K display is faithfully express bright, highly detailed content that fills the entire screen with lifelike images. Connectivity with PCs via a single HDMI cable for displaying 4K2K data.



DX12

DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.



Integrated HDMI with HDCP

Onboard HDMI connector allows full video & audio support. It has industry-leading high definition video quality.



USB 3.1 Gen 1 Type-A

Experience Fastest data transfers at 5 Gbps with USB 3.1 Gen 1--the new latest connectivity standard. Built to connect easily with next-generation components and peripherals, USB 3.1 Gen 1 transfers data 10X faster and backward compatible with previous USB 2.0 components.



SATAIII 6Gbps

SATAIII 6Gbps provides a higher bandwidth to retrieve and transfer HD media. With this super speed data transfer, SATAIII allows an incredible data boost which is 2x faster than the SATA II.



Dual DDR4

The primary advantages of DDR4 over DDR3, include higher module density, lower voltage requirements, coupled with higher data transfer rate.



Moistureproof of PCB

The popularity of PC usage and working environment is getting deteriorating and moist (rural, coastal, etc.). The PCB will be oxidizing easily by damp or absorbed moisture, and ionic migration or CAF (Conductive Anodic Filament) will be generated. Moisture-proof PCB meets high density and high reliability requirements for moisture proof.



Low RdsOn P-Pak MOS

Low resistance design can significantly reduce the current out of energy loss. Low temperature, small size, excellent thermal conductivity.



Super Anti-Surge Protection

BIOSTAR exclusive Anti-Surge design provides the best protection of board and extends the product life. Having the latest model of "Transient Voltage Suppressor" on- board can effectively protect the board circuit, reducing the shocks caused by ESD as well as other damages arising from overvoltage transients to enhance system durability.



Super LAN Surge Protection

Super LAN Surge Protection, providing LAN port with more advanced antistatic protection capabilities by adding an integrated chip to strengthen electrical stability and prevent damage from lightning strikes and electrical surges. SLSP (Super LAN Surge Protection) series motherboard upgrades the existing system protection standards with maximum 4X protection comparing to other board makers.



OC / OV / OH Protection

OC / OV / OH Protection design detects overvoltage conditions and prevents voltage surges from spreading in real time. It also actively cuts off the overvoltage supply to protect your system.



Bitcoin Mining

BIOSTAR offers a perfect choice for "Bitcoin Mining" with more PCI-E slots for users who wish to create a dedicated mining machine and getting a value oriented motherboard that can load up graphic cards is the ideal strategy.



BIO-Flasher

BIO-Flasher is a convenient BIOS update tool. Just launch this tool and put the BIOS on USB pen driver before entering the OS. You can update your BIOS with only a few clicks without preparing an additional floppy disk or other complicated flash utility.



eHot-Line Utiltiy

Integrated e-service automatically sends your technical support request to Biostar Globe tech support without any delay.



BIOScreen Utility

Personalize your desktop with customizable boot logo. BIOScreen is the new feature that lets you personalize and create your own style with unique, custommade boot logo.



HDMI

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

