

B450MHP Motherboard





- Supports AMD Ryzen CPU / APU
- AMD B450 single chip architecture
- Supports 2-DIMM DDR4 up to 64G maximum capacity
- Supports HDMI
- Supports USB 3.2 Gen1

Specifcation	
CPU SUPPORT	Socket AM4 supports AMD A-series APU, Ryzen APU / Ryzen CPU * Please refer to www.biostar.com.tw for CPU support list.
MEMORY	Supports Dual Channel DDR4 1866/2133/2400/2666/2933/3200+(OC) 2 x DDR4 DIMM Memory Slot, Max. Supports up to 64 GB Memory Each DIMM supports non-ECC 8/16/32 GB DDR4 module * Please refer to www.biostar.com.tw for Memory support list.
INTEGRATED VIDEO	By CPU model Supports DX12 Supports HDCP
STORAGE	4 x SATA III Connector (6Gb/s) : Supports AHCI & RAID 0, 1, 10
LAN	Realtek RTL8111H-VB 10/ 100/ 1000 Mb/s auto negotiation, Half / Full duplex capability
AUDIO CODEC	ALC897 7.1 Channels, High Definition Audio
USB	4 x USB 3.2 (Gen1) ports (2 on rear I/Os and 2 via internal headers) 8 x USB 2.0 ports (4 on rear I/Os and 4 via internal headers)
EXPANSION SLOT	AMD Processors 1 x PCIe 3.0 x16 Slot (The bandwidth is depended on CPU) AMD Chipset 2 x PCIe 2.0 x1 Slot
REAR I/O	1 x PS/2 Keyboard/ Mouse 1 x VGA Port 1 x HDMI Port 1 x LAN port 2 x USB 3.2 (Gen1) Ports 4 x USB 2.0 Ports 3 x Audio Jack

INTERNAL I/O	4 x SATA III 6.0Gb/s Connectors 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x 4-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x System Fan Connector 1 x Front Panel Header 1 x Front Audio Header 1 x Clear CMOS Header 1 x COM Serial Header
H/W MONITORING	CPU / System Temperature Monitoring CPU / System Fan Monitoring Smart / Manual CPU Fan Control System Voltage Monitoring
DIMENSION	Micro ATX Form Factor Dimension: 22.6cm x 17.4cm (W x L)
OS SUPPORT	Supports Windows 7(64bit) / 10(64bit) / 11(64bit) *BIOSTAR reserves the right to add or remove support for any OS with or without notice
BUNDLE SOFTWARE	BullGuard
ACCESSORIES	2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x Quick Guide
FEATURES	Supports 100% Solid capacitor BIO-FLASHER Supports BIOS Online Update
	C _X

OVERVIEW	
SOCKET AMA B450	AMD B450 chipset AMD B450 is the high-end chipset for overclockers and tweakers who need robust platforms. This chip provides the ultimate low-level control to its users and delivers ultimate graphics card bandwidth.
HD AUDIO	HD Audio Provides high quality sound with minimal loss of audio fidelity.
HDMI	HDMI 4K2K The new 4K2K resolution enables high-definition image display with four times the resolution of full HD, 4K2K display is faithfully express bright, highly detailed content that fills the entire screen with lifelike images. Connectivity with PCs via a single HDMI cable for displaying 4K2K data.
DX12	DX12 DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.

PCie 3.0	PCIe 3.0 PCIe 3.0 is the ubiquitous and general-purpose PCI Express I/O standard. At 8GT/s bit rate, the interconnect performance bandwidth is doubled over PCIe 2.0, while preserving compatibility with software and mechanical interfaces.
USB 3.2 GENITYPE-A	USB 3.2 Gen1 Type-A USB 3.2 Gen1 delivers a compelling performance boosts and can be used to connect multiple devices without worrying about compatibility. It is capable of data transfer speeds up to 5Gbps and backwards compatible with all existing USB products.
OC TWEAKER	OC TWEAKER OC TWEAKER is the process of adjusting performance settings to optimize system functionality and ensure reliable operation. By increasing the computer is processing speed and GPU frame rates (FPS), it enables the system to handle demanding tasks more effectively, thereby improving user satisfaction.
Moistureproof PCB	Moistureproof of PCB The popularity of PC usage and working environment is getting deteriorating and moist (rural, coastal, etc.). The PCB will be oxidizing easily by damp or absorbed moisture, and ionic migration or CAF (Conductive Anodic Filament) will be generated. Moisture-proof PCB meets high density and high reliability requirements for moisture proof.
Low RdsOn P-Pak MOS	Low RdsOn P-Pak MOS Low resistance design can significantly reduce the current out of energy loss. Low temperature, small size, excellent thermal conductivity.
Stable Lifespan+	100% Solid Caps With armor-plated Biostar Technology, all capacitors are placed with 100% solid capacitors that have a lasting life cycle, durability and stability for crucial components.
ESD PROTECTION	ESD Protection ESD (Electrostatic Discharge) is the major factor to destroy the PC by electrical overstress (EOS) condition. ESD occurred by PC users when touch any devices connect to a PC, which may result in damage to the motherboard or parts. ESD protection is designed to protect the motherboard and equipment from damage by EOS.
USB Polyswitch	USB Polyswitch On board dedicated power fuse to help prevent USB port failure. It prevents USB Port overcurrent and safe guard your system and device lifespan.
OC-OV-OH PROTECTION	OC / OV / OH Protection OC / OV / OH Protection design detects overvoltage conditions and prevents voltage surges from spreading in real time. It also actively cuts off the overvoltage supply to protect your system.



HDMI

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.

*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

Beyond Berrey Bacing to the Furthere

