

# **B550MT Motherboard**





- Socket AM4 support AMD Ryzen™ 3rd Gen (Matisse/ Renoir) and Ryzen™ 4th Gen (Vermeer/ Cezanne) processors
- AMD B550 single chip architecture
- Supports 2-DIMM DDR4 up to 64 GB Memory
- Supports Realtek Gigabit LAN
- Supports Front USB 3.2 Gen2 Type-C
- Supports M.2 (64Gb/s)
- Supports HDMI® 4K resolution

Specifcation	
CPU SUPPORT	Socket AM4 support AMD Ryzen™ 3rd Gen (Matisse/ Renoir) and Ryzen™ 4th Gen (Vermeer/ Cezanne) processors Support for future AMD Ryzen processors with BIOS update * Please refer to www.biostar.com.tw for CPU support list.
MEMORY	4th Gen AMD Ryzen Processors (Vermeer CPUs): Supports Dual Channel DDR4 4400+(OC)/ 4000(OC)/ 3800(OC)/ 3600(OC)/ 3200/ 2933/ 2667/ 2400/2133 4th Gen AMD Ryzen with Radeon Graphics Processors (Cezanne APUs): Supports Dual Channel DDR4 4933+(OC)/ 4800(OC)/ 4600(OC)/ 4400(OC)/ 4000(OC)/ 3800(OC)/3600(OC)/ 3200/ 2933/ 2667/ 2400/ 2133 3rd Gen AMD Ryzen Processors (Matisse CPUs): Supports Dual Channel DDR4 4400+(OC)/ 4000(OC)/ 3800(OC)/ 3600(OC)/ 3200/ 2933/ 2667/ 2400/2133 3rd Gen AMD Ryzen with Radeon Graphics Processors (Renoir APUs): Supports Dual Channel DDR4 4933+(OC)/ 4800(OC)/ 4600(OC)/ 4400(OC)/ 4000(OC)/ 3800(OC)/3600(OC)/ 3200/ 2933/ 2667/ 2400/ 2133 2 x DDR4 DIMM Memory Slot, Max. Supports up to 64 GB Memory Each DIMM supports non-ECC 8/ 16/ 32 GB DDR4 module * Please refer to www.biostar.com.tw for Memory support list.
INTEGRATED VIDEO	By CPU model Supports DX12 Supports HDCP
(ESG)	



Total supports 1 x M.2 socket and 4 x SATA III (6Gb/s) ports 1 x M.2 (M key) Socket (M2M, CPU): Supports M.2 Type 2242/2260/2280 SSD module AMD Ryzen 5000/3000 Series Processors Supports PCle 4.0 x 4 (64Gb/s) & SATA III (6.0Gb/s) SSD AMD Ryzen 5000 G/4000 G Series Processors Supports PCle 3.0 x 4 (32Gb/s) & SATA III (6.0Gb/s) SSD AMD B550 Chipset 4 x SATA III Connectors (6Gb/s): Supports AHCI & RAID 0, 1, 10 + M.2 (M2M, CPU) Socket: The bandwidth is depended on CPU. Supports PCle 4.0 x 4 (64Gb/s) speed, which depends only on Ryzen 3rd Gen Matisse & 4th Gen Vermeer.  LAN Realtek RTLB111H 10/100/1000 Mb/s auto negotiation, Half / Full duplex capability ALCB97 7.1 Channels, High Definition Audio, Hi-Fi (Front) 4 XLSB 3.2 (Gen2) Type-C port (1 via internal headers) 6 x USB 3.2 (Gen2) Type-C port (1 via internal headers) 6 x USB 3.2 (Gen2) prots (4 on rear I/Os and 2 via internal headers) 6 x USB 2.0 ports (2 on rear I/Os and 4 via internal headers) 1 x PCle 4.0 x 16 Siot (x 16 or x 4/x4/x4/x4/x4 mode) or AMD Ryzen 5000 G/4000 G Series Processors 1 x PCle 4.0 x 16 Siot (x 16 or x 4/x4/x4/x4/x4 mode)  AMD Ryzen 5000 G/4000 G Series Processors 1 x PCle 3.0 x 15 Siot (x 16 or x 4/x4/x4/x4/x4 mode) AMD Ryzen 5000 G/4000 G Series Processors 1 x PCle 3.0 x 15 Siot (x 16 or x 4/x4/x4/x4/x4/x4/x4/x4/x4/x4/x4/x4/x4/x4		
AUDIO CODEC  AUDIO CODEC  ALC897 7.1 Channels, High Definition Audio, Hi-Fi (Front)  1 x USB 3.2 (Gen1) ports(4 on rear I/Os and 2 via internal headers) 6 x USB 3.2 (Gen1) ports(4 on rear I/Os and 2 via internal headers) 6 x USB 3.2 (Gen1) ports(4 on rear I/Os and 2 via internal headers) 6 x USB 3.0 ports (2 on rear I/Os and 4 via internal headers)  AMD Ryzen 5000/3000 Series Processors 1 x PCle 4.0 x16 Slot (x16 or x4/x4/x4/x4 mode) or  EXPANSION SLOT  AMD Ryzen 5000 G/4000 G Series Processors 1 x PCle 3.0 x16 Slot (x16 or x8/x4/x4 mode) AMD B550 Chipset 2 x PCle 3.0 x1 Slot * According to different CPUs will have different speeds.  1 x DP Port 1 x HDMI® Port 1 x LAN port 4 x USB 3.2 (Gen1) Ports 2 x USB 2.0 Ports 3 x Audio Jack 4 x SATA III (6.GGb/s) Connectors 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen2) Type-C Header 1 x SPin Power Connector 1 x SPin Power Connector 1 x 24-Pin Power Connector 1 x System Fan Connector 1 x Front Audio Header 1 x TFONT Panel Header 1 x COM Port Header 1 x TFONT Header 1 x TFONT Panel Header 1 x TFONT Panel Fane Gonnector 1 x CPU Fystem Temperature Monitoring CPU / System Tem perature Monitoring CPU / System Tem Monitoring Smart / Manual CPU Fan Control CPU/DOR Voltage Monitoring DIMENSION  Micro ATX Form Factor Dimension: 23.5cm x 20.8cm (W x L)  Supports Windows 10(64bit)/ 11(64bit)  8 Biostar reserves the right to add or remove support for any OS with or without notice.	STORAGE	1 x M.2 (M Key) Socket (M2M_CPU): Supports M.2 Type 2242/ 2260/ 2280 SSD module AMD Ryzen 5000/3000 Series Processors Supports PCle 4.0 x 4 (64Gb/s) & SATA III (6.0Gb/s) SSD AMD Ryzen 5000 G/4000 G Series Processors Supports PCle 3.0 x 4 (32Gb/s) & SATA III (6.0Gb/s) SSD AMD B550 Chipset 4 x SATA III Connectors (6Gb/s): Supports AHCI & RAID 0, 1, 10 * M.2 (M2M_CPU) Socket: The bandwidth is depended on CPU. Supports PCle 4.0 x 4 (64Gb/s) speed, which depends only on Ryzen 3rd Gen Matisse & 4th Gen
AUDIO CODEL 7.1 Channels, High Definition Audio, Hi-Fi (Front) 1 x USB 3.2 (Gen2) Type-C port (1 via internal headers) 6 x USB 2.0 (Gen1) ports(4 on rear I/Os and 2 via internal headers) 6 x USB 2.0 ports (2 on rear I/Os and 4 via internal headers) AMD Ryzen 5000/3000 Series Processors 1 x PCle 4.0 x16 Slot (x16 or x4/x4/x4/x4 mode) or AMD Ryzen 5000 G/4000 G Series Processors 1 x PCle 3.0 x16 Slot (x16 or x8/x4/x4 mode) AMD B550 Chipset 2 x PCle 3.0 x15 Slot x According to different CPUs will have different speeds.  1 x DP Port 1 x HDMie Port 1 x HDMie Port 1 x LAN port 4 x USB 3.2 (Gen1) Ports 2 x USB 2.0 Ports 3 x Audio Jack 4 x SATA III (6.0Gb/s) Connectors 2 x USB 2.0 Ports 1 x USB 3.2 (Gen2) Type-C Header 1 x B-Pin Power Connector 1 x 2-Pin Power Connector 1 x 2-Pin Power Connector 1 x System Fan Connector 1 x Front Panel Header 1 x Front Panel Header 1 x Speaker Header 1 x CMD Fort Header 1 x CMD Fort Header 1 x TPM	LAN	/
G x USB 3.2 (Gen1) ports(4 on rear I/Os and 2 via internal headers) 6 x USB 2.0 ports (2 on rear I/Os and 4 via internal headers)  AMD Ryzen 5000/3000 Series Processors 1 x PCle 4.0 x16 Slot (x16 or x4/x4/x4/x4 mode) or  AMD Ryzen 5000 G/4000 G Series Processors 1 x PCle 3.0 x16 Slot (x16 or x8/x4/x4 mode) AMD B550 Chipset 2 x PCle 3.0 x1 Slot 4 According to different CPUs will have different speeds.  1 x PD Port 1 x LAN port 4 x USB 3.2 (Gen1) Ports 2 x USB 2.0 Ports 3 x Audio Jack  4 x SATA III (6.0G/b/s) Connectors 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x USB 3.2 (Gen2) Type-C Header 1 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x Front Panel Header 1 x Front Audio Header 1 x Front Audio Header 1 x Front Panel Header 1 x CDM Port Header 1 x TPM Header 1	AUDIO CODEC	
EXPANSION SLOT  AMD Ryzen 5000. G/4000 G Series Processors 1 x PCle 3.0 x16 Slot (x16 or x8/x4/x4 mode) AMD B550 Chipset 2 x PCle 3.0 x1 Slot * According to different CPUs will have different speeds.  1 x DP Port 1 x HDMI® Port 1 x LAN port 4 x USB 3.2 (Gen1) Ports 2 x USB 2.0 Ports 3 x Audio Jack  4 x SATA III (6.0Gb/s) Connectors 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x USB 3.2 (Gen2) Type-C Header 1 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x 24-Pin Power Connector 1 x System Fan Connector 1 x Front Audio Header 1 x CPU Fan Connector 1 x Front Panel Header 1 x COM Port Header 1 x COM Port Header 1 x COM Port Header 1 x TPM Hauder 1 x TPM Header 2 CPU / System Temperature Monitoring CPU/DDR Voltage Monitoring DIMENSION Micro ATX Form Factor Dimension: 23.5cm x 20.8cm ( W x L ) Supports Windows 10(64bit)/ 11(64bit) 8 Biostar reserves the right to add or remove support for any OS with or without notice.	USB	6 x USB 3.2 (Gen1) ports(4 on rear I/Os and 2 via internal headers) 6 x USB 2.0 ports (2 on rear I/Os and 4 via internal headers)
REAR I/O  1 x HDMI® Port 1 x LAN port 4 x USB 3.2 (Gen1) Ports 2 x USB 2.0 Ports 3 x Audio Jack  4 x SATA III (6.0Gb/s) Connectors 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x USB 3.2 (Gen2) Type-C Header 1 x S-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x Front Audio Header 1 x Front Audio Header 1 x Front Audio Header 1 x Clear CMOS Header 1 x COM Port Header 1 x TPM Header 2 CPU / System Fan Monitoring 3 Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring  DIMENSION  Micro ATX Form Factor Dimension: 23.5cm x 20.8cm (W x L)  Supports Windows 10(64bit)/ 11(64bit)  *Biostar reserves the right to add or remove support for any OS with or without notice.	EXPANSION SLOT	1 x PCle 4.0 x16 Slot (x16 or x4/x4/x4 mode) or  AMD Ryzen 5000 G/4000 G Series Processors  1 x PCle 3.0 x16 Slot (x16 or x8/x4/x4 mode)  AMD B550 Chipset  2 x PCle 3.0 x1 Slot  * According to different CPUs will have different speeds.
2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x USB 3.2 (Gen2) Type-C Header 1 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x System Fan Connector 1 x Front Panel Header 1 x Front Audio Header 1 x Speaker Header 1 x Clear CMOS Header 1 x COM Port Header 1 x TPM Header CPU / System Temperature Monitoring CPU / System Temperature Monitoring CPU / System Fan Monitoring Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring  DIMENSION Micro ATX Form Factor Dimension: 23.5cm x 20.8cm ( W x L ) Supports Windows 10(64bit)/ 11(64bit) *Biostar reserves the right to add or remove support for any OS with or without notice.	REAR I/O	1 x HDMI® Port 1 x LAN port 4 x USB 3.2 (Gen1) Ports 2 x USB 2.0 Ports
H/W MONITORING  CPU / System Fan Monitoring Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring  DIMENSION  Micro ATX Form Factor Dimension: 23.5cm x 20.8cm ( W x L )  Supports Windows 10(64bit)/ 11(64bit)  *Biostar reserves the right to add or remove support for any OS with or without notice.	INTERNAL I/O	2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x USB 3.2 (Gen2) Type-C Header 1 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x System Fan Connector 1 x Front Panel Header 1 x Front Audio Header 1 x Speaker Header 1 x Clear CMOS Header 1 x COM Port Header
OS SUPPORT  Supports Windows 10(64bit)/ 11(64bit)  *Biostar reserves the right to add or remove support for any OS with or without notice.	(ECC	CPU / System Fan Monitoring Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring
		Supports Windows 10(64bit)/ 11(64bit)  *Biostar reserves the right to add or remove support for any OS with or without
	BUNDLE SOFTWARE	

**ACCESSORIES** 

2 x SATA Cable

1 x I/O Shield

1 x DVD Driver

1 x Quick Guide

## **OVERVIEW**



# AMD B550 chipset

AMD B550 is the high-end chipset for overclockers and tweakers who need robust platforms. This chip provides the ultimate low-level control to its users and delivers ultimate graphics card bandwidth. It also supports PCI-E Gen4 bandwidth



### **HD** Audio

Provides high quality sound with minimal loss of audio fidelity.



### Hi-Fi Ground

BIOSTAR Hi-Fi Ground (Golden Line) is noise-blocking multi-layer PCB design to isolates analog audio signals from digital sources. Unique PCB layout is ideal for exceptional clarity and high fidelity sound.



#### HDMI® 4K2K

The new 4K2K resolution enables high-definition image display with four times the resolution of full HD, 4K2K display is faithfully express bright, highly detailed content that fills the entire screen with lifelike images. Connectivity with PCs via a single HDMI® cable for displaying 4K2K data.



## **DisplayPort**

DisplayPort is a digital display interface developed by the Video Electronics Standards Association (VESA). The interface is primarily used to connect a video source to a display device such as a computer monitor, though it can also be used to carry audio.



#### **DX12**

DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.



#### PCle M.2

PCIe M.2 32Gb/s delivers the highest bandwidth and lower latency. It is 3 times faster compared with PCIe M.2 10Gb/s.



## PCle 3.0

PCIe 3.0 is the ubiquitous and general-purpose PCI Express I/O standard. At 8GT/s bit rate, the interconnect performance bandwidth is doubled over PCIe 2.0, while preserving compatibility with software and mechanical interfaces.



## SATAIII 6Gbps

SATAIII 6Gbps provides a higher bandwidth to retrieve and transfer HD media. With this super speed data transfer, SATAIII allows an incredible data boost which is 2x faster than the SATA II.



### **Dual DDR4**

The primary advantages of DDR4 over DDR3, include higher module density, lower voltage requirements, coupled with higher data transfer rate.



### **PCIe 4.0**

PCIe 4.0 is the ubiquitous and general-purpose PCI Express I/O standard. At 16GT/s bit rate, the interconnect performance bandwidth is doubled over PCIe 3.0, while preserving compatibility with software and mechanical interfaces.



## PCIe 4.0 M.2

PCle 4.0 M.2 delivers the highest bandwidth and lower latency. It is 2 times faster compared with PCle 3.0 M.2 .



# USB 3.2 Gen1 Type-A

USB 3.2 Gen1 delivers a compelling performance boosts and can be used to connect multiple devices without worrying about compatibility. It is capable of data transfer speeds up to 5Gbps and backwards compatible with all existing USB products.



# Super Durable Solid Caps

The best quality solid state capacitors with ultra low ESR design, the Super Durable Solid Caps doubles the lifespan.



# Moistureproof PCB

The PCB will be oxidizing easily by damp or absorbed moisture, and ionic migration or CAF (Conductive Anodic Filament) will be generated. Moisture proof PCB meets high density and high reliability requirements for moisture proof.



## OC / OV / OH Protection

OC / OV / OH Protection design detects overvoltage conditions and prevents voltage surges from spreading in real time. It also actively cuts off the overvoltage supply to protect your system.



#### **UEFI BIOS**

Unified Extensible Firmware Interface (UEFI) is a brand new framework that provides a revolutionary interface. It is a modern clear and easy-to-use graphical user interface. The UEFI comes with a colorful easy-understand icons lead users into the setup layer directly.



### **BIO-Flasher**

BIO-Flasher is a convenient BIOS update tool. Just launch this tool and put the BIOS on USB pen driver before entering the OS. You can update your BIOS with only a few clicks without preparing an additional floppy disk or other complicated flash utility.



#### A.I FAN

With A.I FAN users can ensure that their gaming PC can maintain its performance while staying cool. According to different cooling needs and usage scenarios, users can control speed modes. Allows users to have more customizability of fan modes and automatically detects different temperatures to make fan operate at defined speed for optimal cooling performance.



## **Smart Update**

Biostar Smart Update is a utility that can help users run online update. It can download the drivers for your motherboard from Biostar official website and install them automatically.



### **HDMI®**

The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® Logo are trademarks or registered trademarks of HDMI® Licensing Administrator, Inc. in the United States and other countries.

\*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!



