

# H310MHG Motherboard



- Supports 8th & 9th Generation Intel® Core  $^{\text{\tiny TM}}$  Processor
- Intel H310 single chip architecture
- Support Dual Channel DDR4 2666/2400/2133/1866 MHz
- Support HDMI 4K resolution
- Support GbE LAN
- Support USB 3.2 Gen1

Specifcation		
CPU SUPPORT	9th Gen Intel® Core™ i9 LGA 1151 Processor 9th Gen Intel® Core™ i5 LGA 1151 Processor 9th Gen Intel® Core™ i3 LGA 1151 Processor 8th Gen Intel® Core™ i7 LGA 1151 Processor 8th Gen Intel® Core™ i5 LGA 1151 Processor 8th Gen Intel® Core™ i3 LGA 1151 Processor 8th Gen Intel® Pentium® LGA 1151 Processor 8th Gen Intel® Pentium® LGA 1151 Processor 8th Gen Intel® Celeron® LGA 1151 Processor Waximum CPU TDP (Thermal Design Power): 95Watt * Please refer to www.biostar.com.tw for CPU support list.	
MEMORY	Support Dual Channel DDR4 2666/ 2400/ 2133/ 1866 MHz 2 x DDR4 DIMM Memory Slot Max. Supports up to 32GB Memory	
INTEGRATED VIDEO	Supports DX12 Supports HDCP	
STORAGE	4 x SATA III Connectors (6Gb/s) 1 x M.2 (M Key) Connector(10Gb/s) : Supports PCI-E (10Gb/s) & SATA III (6Gb/s)SSD	
LAN	Realtek RTL8111H - 10/100/1000Mb/s Controller	
AUDIO CODEC	Realtek ALC887 7.1-Channel HD Audio Support HD Audio	
USB	4 x USB 3.2 Gen1 Port (2 on rear I/Os and 2 via internal header) 6 x USB 2.0 Port (4 on rear I/Os and 2 via internal header)	
EXPANSION SLOT	1 x PCI-E 3.0 x16 Slot 2 x PCI-E 2.0 x1 Slot 1 x PCI Slot	

REAR I/O	1 x PS/2 Mouse 1 x PS/2 Keyboard 2 x USB 3.2 Gen1 Ports 4 x USB 2.0 Port 1 x COM Port 1 x HDMI Connector 1 x DVI-D Connector 1 x VGA Port 1 x LAN Port 3 x Audio Jacks
INTERNAL I/O	1 x USB 3.2 Gen1 Header (each header supports 2 USB 3.2(Gen1) ports) 1 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 4 x SATA III Connector (6Gb/s) 1 x Front Audio Header 1 x Front Panel Header 1 x CPU Fan Connector 2 x System Fan Connector 1 x Chassis Instruction Header 1 x TPM Header 1 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x Clear CMOS Header 1 x COM Port Header 1 x Printer Port Header
H/W MONITORING	CPU / System Temperature Monitoring CPU / System Fan Monitoring Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring
DIMENSION	Micro ATX Form Factor Dimension: 24.4cm x 18.8cm ( W x L )
OS SUPPORT	Supports Windows 11(64bit) / 10(64bit) Windows 7 ** BIOSTAR reserves the right to add or remove support for any OS with or without notice.
BUNDLE SOFTWARE	
ACCESSORIES	2 x SATA Cable 1 x I/O Shield 1 x Fully Setup Driver CD 1 x Quick Guide
FEATURES	BIO-FLASHER

# **OVERVIEW**



# Intel H310 chipset

The Intel® H310 chipset is a single-chipset design to support socket 1151 Intel® 8th generation Intel® Core™ processor-based platform. Provides excellent performance and increased bandwidth and stability. The PC platform features improved adaptive performance that adds speed when you need it. When combined with advanced system responsiveness, the platform delivers the ultimate PC experience.



### DVI

DVI is better than VGA for LCD displays since it is digital while VGA is analog. For LCD displays, the picture is digitized pixel per pixel. Through DVI, the panel gets data for each pixel, so the picture generated in the Graphics device matches the pixels on the panel itself.



### DX12

DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.



## Integrated HDMI with HDCP

Onboard HDMI connector allows full video & audio support. It has industry-leading high definition video quality.



## PCIe M.2 (10Gb/s)

it delivers faster performance compared with SATA interface 6Gb/s.



### PCIe 3.0

PCIe 3.0 is the ubiquitous and general-purpose PCI Express I/O standard. At 8GT/s bit rate, the interconnect performance bandwidth is doubled over PCIe 2.0, while preserving compatibility with software and mechanical interfaces.



## SATAIII 6Gbps

SATAIII 6Gbps provides a higher bandwidth to retrieve and transfer HD media. With this super speed data transfer, SATAIII allows an incredible data boost which is 2x faster than the SATA II.



## USB 3.2 Gen1 Type-A

USB 3.2 Gen1 delivers a compelling performance boosts and can be used to connect multiple devices without worrying about compatibility. It is capable of data transfer speeds up to 5Gbps and backwards compatible with all existing USB products.



## 100% Solid Caps

With armor-plated Biostar Technology, all capacitors are placed with 100% solid capacitors that have a lasting life cycle, durability and stability for crucial components.



### **UEFI BIOS**

Unified Extensible Firmware Interface (UEFI) is a brand new framework that provides a revolutionary interface. It is a modern clear and easy-to-use graphical user interface. The UEFI comes with a colorful easy-understand icons leads users into the setup layer directly.



### **HDMI**

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.

\*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!



