

# H410MHG Motherboard



- Supports 10th Generation Intel Core™ Processor
- Intel H410 single chip architecture
- Supports 2-DIMM DDR4- 1866/ 2133/ 2400/ 2666/ 2800/ 2933 up to 64 GB Memory max capacity
- Supports PCle M.2 (10Gb/s)
- Supports HDMI 4K resolution
- Supports GbE LAN

Specifcation			
CPU SUPPORT	Support for 10th Generation Intel® Core™ i9 processors/Intel® Core™ i7 processors/Intel® Core™ i5 processors/Intel® Core™ i3 processors/Intel® Pentium® processors/Intel® Celeron® processors in the LGA1200 package * Please refer to www.biostar.com.tw for CPU support list.		
MEMORY	Supports Dual Channel DDR4 1866/ 2133/ 2400/ 2666/ 2800/ 2933 2 x DDR4 DIMM Memory Slot, Max. Supports up to 64 GB Memory Each DIMM supports non-ECC 4/8/16/32GB DDR4 module * Please refer to Memory Support List for more information. Core (i9/i7) support DDR4 up to 2933 MHz; Core (i5/i3), Pentium and Celeron support DDR4 up to 2666 MHz.		
INTEGRATED VIDEO	By CPU model Supports DX12 Supports HDCP		
STORAGE	Total supports 1 x M.2 slots and 4 x SATA III(6Gb/s) ports 1 x PCIe-M2 socket , with M key, type 2242/2260/2280 storage devices support SATA & PCIE 3.0 x 2 mode 4 x SATA III (6Gb/s) * When using SATA SSD module on M.2(PCIe-M2)slot, the SATA_1 connector will be disabled.		
LAN	RTL8111H 10/ 100/ 1000 Mb/s auto negotiation, Half / Full duplex capability		
AUDIO CODEC	ALC887 7.1 Channels, High Definition Audio		
USB	4 x USB 3.2(Gen1) ports (2 on rear I/Os and 2 via internal headers) 8 x USB 2.0 ports (4 on rear I/Os and 4 via internal headers)		
EXPANSION SLOT	1 x PCI Slot 2 x PCIe 3.0 x 1 Slots 1 x PCIe 3.0 x 16 Slot		

REAR I/O  1 x PS/2 Keyboard 1 x PS/2 Mouse 1 x DVI-D Port 1 x VGA Port 1 x HDMI Port 1 x COM Port 2 x USB 3.2 (Gen1) Ports 4 x USB 2.0 Ports 1 x LAN port 3 x Audio Jack 4 x SATA III Connectors (6Gb/s)
4 x SATA III Connectors (6Gh/s)
INTERNAL I/O  IN
H/W MONITORING  CPU / System Temperature Monitoring CPU / System Fan Monitoring Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring
DIMENSION Micro ATX Form Factor Dimension: 19.1cm x 24.4cm ( W x L )
OS SUPPORT Supports Windows 10 (64bit) / 11(64bit)  *Biostar reserves the right to add or remove support for any OS with or without notice.
BUNDLE SOFTWARE BullGuard
ACCESSORIES  2 x SATA Cable 1 x I/O Shield 1 x DVD Driver 1 x Quick Guide
FEATURES Supports 100% Solid capacitor

## **OVERVIEW**



## Intel H410 chipset

With the Intel® H410 chipset and the 10<sup>th</sup> generation Intel® Core™ processors, you will immediately be at the forefront of the battlefield, fueled by mind-blowing power and performance. From content creation to gaming, the Intel H410 chipset provides you with the power and performance you need.



### **HD** Audio

Provides high quality sound with minimal loss of audio fidelity.



#### HDMI 4K2K

The new 4K2K resolution enables high-definition image display with four times the resolution of full HD, 4K2K display is faithfully express bright, highly detailed content that fills the entire screen with lifelike images. Connectivity with PCs via a single HDMI cable for displaying 4K2K data.



#### DVI

DVI is better than VGA for LCD displays since it is digital while VGA is analog. For LCD displays, the picture is digitized pixel per pixel. Through DVI, the panel gets data for each pixel, so the picture generated in the Graphics device matches the pixels on the panel itself.



#### **DX12**

DirectX 12 introduces the next version of Direct3D, the graphics API at the heart of DirectX. Direct3D is one of the most critical pieces of a game or game engine, and we've redesigned it to be faster and more efficient than ever before. Direct3D 12 enables richer scenes, more objects, and full utilization of modern GPU hardware.



## Integrated HDMI with HDCP

Onboard HDMI connector allows full video & audio support. It has industry-leading high definition video quality.



## PCle M.2 (10Gb/s)

it delivers faster performance compared with SATA interface 6Gb/s.



#### PCIe 3.0

PCIe 3.0 is the ubiquitous and general-purpose PCI Express I/O standard. At 8GT/s bit rate, the interconnect performance bandwidth is doubled over PCIe 2.0, while preserving compatibility with software and mechanical interfaces.



## **SATAIII 6Gbps**

SATAIII 6Gbps provides a higher bandwidth to retrieve and transfer HD media. With this super speed data transfer, SATAIII allows an incredible data boost which is 2x faster than the SATA II.



## **Dual DDR4**

The primary advantages of DDR4 over DDR3, include higher module density, lower voltage requirements, coupled with higher data transfer rate.



## USB 3.2 Gen1 Type-A

USB 3.2 Gen1 delivers a compelling performance boosts and can be used to connect multiple devices without worrying about compatibility. It is capable of data transfer speeds up to 5Gbps and backwards compatible with all existing USB products.



## 5 Phase Power Phase Design

5-phase VRM design with high quality power components such as low RDS (on) Mosfet for lower temperature has the advantage to raise the overclocking ability.

Stable, III	CITOR espan+	100% Solid With armor-plat capacitors that components.
BullGua	ırd⁻	BullGuard Internet features on the Backup for your Mode for a sear Browsing and m
UEF BIO		UEFI BIOS Unified Extensil provides a revouser interface. into the setup la

## d Caps

ted Biostar Technology, all capacitors are placed with 100% solid have a lasting life cycle, durability and stability for crucial

## Internet Security (90 days FREE trial)

net Security comes with the broadest line-up of internet security market, including: a cutting-edge dual Antivirus engine, Online r precious files, PC Tune Up to speed up your system, a Game mless gaming experience, Parental Control, Firewall, Safe nany more. Make the most of your digital life with Bullguard!

ble Firmware Interface (UEFI) is a brand new framework that olutionary interface. It is a modern clear and easy-to-use graphical The UEFI comes with a colorful easy-understand icons leads users aver directly.

#### **BIO-Flasher**

BIO-Flasher is a convenient BIOS update tool. Just launch this tool and put the BIOS on USB pen driver before entering the OS. You can update your BIOS with only a few clicks without preparing an additional floppy disk or other complicated flash utility.

## **HDMI**

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.

\*The specification and pictures are subject to change without notice and the package contents may differ by area or your motherboard version!

